

City of Leavenworth
700 US Hwy 2
Leavenworth, WA 98826
Telephone: (509) 548-5275

APPLICATION TO PERFORM WORK ON CITY STREET RIGHT-OF-WAY

NAME OF APPLICANT _____ DATE _____

The undersigned hereby applies for permission to _____

Pursuant to franchise _____ Dated _____

The estimated time required for completion of the above work is _____ which the petitioner agrees to prosecute with all diligence and speed with due regard for the rights, interests and conveniences of the public.

Petitioner further agrees to perform the work in strict compliance with the provisions enumerated below and states that he has read and will adhere to the general provisions applicable to permits contained on the reverse side of this form.

PROJECT ADDRESS _____

ADDRESS _____

PHONE _____ Signature _____ Title _____

FAX: _____ Job No. _____

PERMIT

Subject to all the terms, specifications, conditions, and provisions written or printed below or on any part of this form.

PERMISSION IS HEREBY GRANTED the above applicant to: _____

1. The grantee shall cut existing asphalt surface on a true line using a saw or jackhammer with an asphalt bit, to prevent damage to existing pavement. Cut shall be made at least six (6) inches wider than trench.
2. The grantee shall, when placing his or her facility within any portion of the roadbed, the trench shall be backfilled in horizontal layers not to exceed six (6) inches in loose thickness, except that the layers of the top two (2) feet from profile street grade shall not exceed four (4) inches in loose thickness. Each layer of the entire fill shall be compacted to not less than ninety-five percent (95%) of the maximum density. In no case will "water settling" be allowed. If in opinion of the Director of Public Works that compaction is inadequate he may order suitable compaction test to be performed by an independent soils laboratory. If the compaction is found to meet specification, the city shall pay for testing, of the compaction is found to be inadequate; the grantee shall pay for testing and remove and replace backfill in the proper manner.
3. The street substructure and surfacing shall consist of .5' of ballast (1 1/2 inch minus, W.S.D.O.T. specification), .3' of crushed surfacing (5/8 inch minus, W.S.D.O.T. specification) overlaid with .2' of hot asphalt concrete (Class B or G, W.S.D.O.T. specification). The ballast and crushed surfacing shall meet the compaction requirements stated in Item 2. The asphalt concrete shall not be lapped over existing pavement and shall be compacted and smoothed using a roller or vibratory plate only.
4. When the existing pavement is Portland Cement Concrete, the grantee shall install the same substructure as required in Item 3 and the surfacing shall consist of six (6) inches of Portland Cement Concrete "Class A" W.S.D.O.T. specification. The surface shall have a broomed texture. The concrete patch shall be treated with a curing compound as specified by the W.S.D.O.T.
5. If determined necessary by the Director of Public Works, any or all of the excavated material shall be removed and replaced with suitable material by the grantee at his expense.
6. All manholes, valve covers, monuments, catch basins and like appurtenances shall be constructed at such an elevation to conform to pavement or shoulder slope. Any existing appurtenances moved or damaged by the grantee shall be restored to its original cross-section and condition.
7. Trenches excavated in shoulder areas shall be compacted in the same manner as 2 and the upper twelve (12) inches shall consist of ballast as in 3. The shoulder slope shall be restored to the existing slope.

A bond in the amount of _____ is required to insure compliance with the above conditions, said bond to be kept in full force and effect for a period of _____ years following completion of work authorized by this permit.

No work shall be done under this permit until the party of parties to whom it is granted shall have communicated with and received instructions from the Director of Public Works. Phone: 509/548-5275.

This permit shall be void unless the work herein contemplated shall have been completed before _____, 20____.

APPROVED _____ DATE _____
BY _____

It is the responsibility of the applicant to notify all utilities and private property owners when such property is liable to injury or damage through the performance of the above work and the applicant shall make all necessary arrangements relative to the protection of such property and/or utilities.

UTILITY DAMAGE IS COSTLY. CALL BEFORE YOU DIG - 1-800-424-5555
WORK SAFELY / THINK SAFETY

1) Applicant - White
2) Public Works - Canary